

Loft Access Hatches

New range of FD60 fire rated steel loft doors range available now.

Drop down, FD60 fire rated, steel loft access hatch

IFZ2.60 (SD) budget lock

IFZ2.65 (SDL) Euro Lock



Spare budget lock keys available to order – IFZ2.60ACKEY

Push up, FD60 fire rated, steel loft access hatch

IFZ2.80 (SP1)



A one hour fire rated trap, which has an attractive contemporary design and many innovative features that set it apart from all other traps, including one of the largest clear openings available to the market.

The durable zintec steel has a powder coated smooth white maintenance free finish, projecting only 7mm into the ceiling space. The concealed continuous hinges and completely flush "lid to frame" offer a simplistic, unobtrusive look.

The SD is fitted with a unique hardened steel quarter-turn catch with a neat tri-drive and built-in chamfer, for a smooth closing action and high compression. The lid weight of only 5.8kg coupled with an access key, allows opening from floor level.

In addition to the inner draught and vapour seal between the lid and frame, a concealed outer seal between the frame and ceiling negates the need for costly on site sealant. This saves time, costs and assists in the ease of decoration of the ceiling up to the frame.

Model	Ceiling Cutout	Clear Opening (Once Installed)	"U" Value	Part "L" Compliant	NHBC Compliant	UKAS Accredited Air Tested	1 Hour Fire Rated	Key Lockable	Weight
SD	755 x 555mm	630 x 520mm	0.32	✓	✓	✓	✓	-	7.6kg
SDL	755 x 555mm	630 x 520mm	0.32	✓	✓	✓	✓	✓	7.6kg
Model	Ceiling Cut-out	Clear Opening (Once Installed)	"U" Value	Part "L" Compliant	NHBC Compliant	UKAS Accredited Air Tested	1 Hour Fire Rated	Weight	
SP1	555 x 555mm	520 x 520mm	0.32	✓	✓	✓	✓	4.8kg	

Please note the IFZ2.70 and IFZ2.75 are no longer available

For samples or further technical information please contact our Sales Office on 01924-438112.