

Kitemark™ Certificate

This is to certify that:

Ian Firth Hardware Ltd
Lady Ann House
Shaw Cross Business Park
Dewsbury
WF12 7RD
United Kingdom

Holds Certificate Number:

KM 647663

In respect of:

BS 8529 / PAS24
Enhanced Security Composite Door Fabricator

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.



For and on behalf of BSI:

Gary Fenton, Global Product Certification Director

First Issued: 05/02/2016

Latest Issue: 27/01/2017



Kitemark™ Certificate

No. KM 647663

BS 8529:2010 / PAS 24:2012 - General and enhanced security performance requirements for Composite door assemblies.

This Certificate covers the following residential door system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

Lake Collection X Range Composite Residential Door System

Fabricated and installed in accordance with the latest issue of the following controlled manual(s):
IMS Management System Manual

System description

The door assemblies are Xinyu GRP slabs, with either PVC-U extruded outer frames as supplied by either Eurocell or Duraflex, Winkhaus Eco Frame Redwood timber frames. Open in or out, hinged on outer frame or mullion, ODL tri-sys cassette glazed or Auotplas screw-fit glazed laminated on one pane to Class P1A. Door assemblies are classified as DK or DKT and can include letter plates.

Hardware Options

Lock: Yale YS170, Gridlock E,C, N and P Series, Winkhaus Thunderbolt or Trulock
Hinges: IFL73.20 Tianbao 3-D adjustable, Fab 'n' Fix Haven, IFL.19/20/21 (Timber frames only) Winkhaus cranked Ball Bearing (EcoFrame only)
Handles: Hoppe Atlanta, IFH12.99 Lucca, IFH12.49 Sienna with Winkhaus Armourshield, IFH12.89 Venice with Winkhaus Armourshield
Cylinder: Ian Firth IFM4.56 or 57, Yale Kitemarked Cylinder or any Kitemarked combination achieving a total of 3* performance rating.
Threshold: Stormguard slimline aluminium. Slimline fixed to frame, Proprietary Eze access
Letter plate: IFH4.30, IFH4.35 Premier or Fab 'n' Fix NuMail fitted with letterplate cowl IFH4.27 or IFH4.31..

Size Limitations and Performance Characteristics

Door Type	Length (mm) Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for doors with approved outer frame and sash profiles:						
Single leaf doors	914	2013	2	1A	A2	800
Single leaf sidelight Double leaf sidelight	1500 1900	2013	2	1A	A2	800
Fanlight	2814	250	2	1A	A2	800

First Issued: 05/02/2016

Latest Issue: 27/01/2017

Page: 2 of 3

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

Kitemark™ Certificate

No. KM 647663

BS 8529:2010 / PAS 24:2012 - General and enhanced security performance requirements for Composite door assemblies.

This Certificate covers the following residential door system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

Lake Collection N Range Composite Residential Door System

Fabricated and installed in accordance with the latest issue of the following controlled manual(s):
IMS Management System Manual

System description

The door assemblies are NanYa GRP slabs, with either PVC-U extruded outer frames as supplied by either Eurocell or Duraflex, Winkhaus Eco Frame Redwood timber frames. Open in or out, hinged on outer frame or mullion, ODL tri-sys cassette glazed or Auotplas screw-fit glazed laminated on one pane to Class P1A. Door assemblies are classified as DK or DKT and can include letter plates.

Hardware Options

Lock: Yale YS170, Gridlock E,C, N and P Series, Winkhaus Thunderbolt or Trulock
Hinges: IFL73.20 Tianbao 3-D adjustable, Fab 'n' Fix Haven, IFL.19/20/21 (Timber frames only) Winkhaus cranked Ball Bearing (EcoFrame only)
Handles: Hoppe Atlanta, IFH12.99 Lucca, IFH12.49 Sienna with Winkhaus Armourshield, IFH12.89 Venice with Winkhaus Armourshield
Cylinder: Ian Firth IFM4.56 or 57, Yale Kitemarked Cylinder or any Kitemarked combination achieving a total of 3* performance rating.
Threshold: Stormguard slimline aluminium. Slimline fixed to frame, Proprietary Eze access
Letter plate: IFH4.30, IFH4.35 Premier or Fab 'n' Fix NuMail fitted with letterplate cowl IFH4.27 or IFH4.31..

Size Limitations and Performance Characteristics

Door Type	Length (mm) Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for doors with approved outer frame and sash profiles:						
Single leaf doors	914	2013	2	1A	A2	800
Single leaf sidelight Double leaf sidelight	1500 1900	2013	2	1A	A2	800
Fanlight	2814	250	2	1A	A2	800

First Issued: 05/02/2016

Latest Issue: 27/01/2017

Page: 3 of 3

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).