




Typical Doorset Weight Guide



 Un glazed	838mm = 48kg 914mm = 51kg	838mm = 54kg 914mm = 57kg <i>Fanlight 2320mm tall</i>	838mm = 76kg 914mm = 79kg <i>Sidelight 450mm wide</i>	838mm = 104g 914mm = 107kg <i>Sidelights each 450mm wide</i>
 One Lite	838mm = 50kg 914mm = 53kg	838mm = 56kg 914mm = 59kg <i>Fanlight 2320mm tall</i>	838mm = 78kg 914mm = 81kg <i>Sidelight 450mm wide</i>	838mm = 102g 914mm = 109kg <i>Sidelights each 450mm wide</i>
 Half Glazed	838mm = 57kg 914mm = 60kg	838mm = 63kg 914mm = 66kg <i>Fanlight 2320mm tall</i>	838mm = 85kg 914mm = 88kg <i>Sidelight 450mm wide</i>	838mm = 113g 914mm = 116kg <i>Sidelights each 450mm wide</i>

All weights given are approximate and to be used as a guide only. All doorsets are 2 person lift.

All doors have the multi-point lock bolts thrown (top & bottom) and latch bolt. These hold door in frame during transportation. To open the door, use spindle or handle to press down and release bolts. Do not attempt to move a doorset without the top and bottom bolts engaged. Best practice would be to carry single doorsets horizontally, preferably with door leaf opening upwards.

Sidelight Combination Frames are supplied with nylon webbing temporary grip handles to help with manoeuvring doorsets on site. Best practice would be to keep such doorsets vertical when moving, sliding where possible. Extra care should be taken to ensure the sill does not get damaged during manoeuvring.

